PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

Procurement of GOODS

Government of the Republic of the Philippines

PR No. 23010110 – Supply and Delivery of Hospital Equipment (OR Lights & 4 others)

Sixth Edition July 2020

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the particular Procurement Project.
- b. Specific details, such as the "name of the Procuring Entity" and "address for bid submission," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.

- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.
- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

| Gloss | ary of Acronyms, Terms, and Abbreviations | 4 |
|--------|--|----|
| Sectio | on I. Invitation to Bid | 7 |
| Sectio | on II. Instructions to Bidders | 8 |
| 1. | Scope of Bid | 11 |
| 2. | Funding Information | 11 |
| 3. | Bidding Requirements | 11 |
| 4. | Corrupt, Fraudulent, Collusive, and Coercive Practices | 11 |
| 5. | Eligible Bidders | 12 |
| 6. | Origin of Goods | 12 |
| 7. | Subcontracts | 12 |
| 8. | Pre-Bid Conference | 12 |
| 9. | Clarification and Amendment of Bidding Documents | 12 |
| 10. | Documents comprising the Bid: Eligibility and Technical Components | 13 |
| 11. | Documents comprising the Bid: Financial Component | 13 |
| 12. | Bid Prices | 13 |
| 13. | Bid and Payment Currencies | 14 |
| 14. | Bid Security | 14 |
| 15. | Sealing and Marking of Bids | 14 |
| 16. | Deadline for Submission of Bids | 15 |
| 17. | Opening and Preliminary Examination of Bids | 15 |
| 18. | Domestic Preference | 15 |
| 19. | Detailed Evaluation and Comparison of Bids | 15 |
| 20. | Post-Qualification | 16 |
| 21. | Signing of the Contract | 16 |
| Sectio | on III. Bid Data Sheet | 17 |
| Sectio | on IV. General Conditions of Contract | 19 |
| 1. | Scope of Contract | 20 |
| 2. | Advance Payment and Terms of Payment | 20 |
| 3. | Performance Security | 20 |
| 4. | Inspection and Tests | 20 |
| 5. | Warranty | 21 |
| 6. | Liability of the Supplier | 21 |
| Sectio | on V. Special Conditions of Contract | 22 |
| Sectio | on VI. Schedule of Requirements | 26 |
| | on VII. Technical Specifications | |
| | on VIII. Checklist of Technical and Financial Documents | |

Glossary of Acronyms, Terms, and Abbreviations

ABC – Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF - Cost Insurance and Freight.

CIP – Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

EXW - Ex works.

FCA – "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project—Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC – Government-owned and/or –controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB – Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national

buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.

Section I. Invitation to Bid



REPUBLIC OF THE PHILIPPINES PROVINCE OF CAMARINES NORTE Daet

BIDS AND AWARDS COMMITTEE

Invitation to Bid for

PR No. 23010110 – Supply and Delivery of Hospital Equipment (OR Lights & 4 others)

- 1. The Provincial Government of Camarines Norte, through the General Fund Capital Outlay CY 2023 intends to apply the sum of Nine Million Nine Hundred Fifty-Seven Thousand Seven Hundred Twenty Pesos (P9,957,720.00) being the Approved Budget for the Contract (ABC) to payments under the contract for PR No. 23010110 Supply and Delivery of Hospital Equipment (OR Lights & 4 others). Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The Provincial Government of Camarines Norte now invites bids for Supply and Delivery of Hospital Equipment (OR Lights & 4 others).
 - Delivery of the Goods is required within 60 calendar days. Bidders should have completed, within 5 years from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II. Instructions to Bidders.
- 3. Bidding will be conducted through open competitive bidding procedures using non-discretionary "pass/fail" criterion as specified in the 2016 Revised Implementing Rules and Regulations (IRR) of Republic Act 9184 (RA 9184), otherwise known as the "Government Procurement Reform Act."
 - Bidding is restricted to Filipino citizens/sole proprietorships, partnerships, or organizations with at least sixty percent (60%) interest or outstanding capital stock belonging to citizens of the Philippines, and to citizens or organizations of a country the laws or regulations of which grant similar rights or privileges to Filipino citizens, pursuant to RA 5183.
- 4. Bidders may obtain further information from the *Provincial Government of Camarines Norte* and inspect the Bidding Documents at the address given below from 8:00a.m. to 5:00p.m., Monday to Friday.
- 5. A complete set of Bidding Documents may be acquired by interested bidders on February 24 March 21, 2023 at the Provincial Capitol Building, Daet, Camarines Norte and from the website of the Philippine Government Electronic Procurement System (PhilGEPS) upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of Ten Thousand Pesos (P10,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees in person.
- 6. The *Provincial Government of Camarines Norte* will hold a Pre-Bid Conference on *March 7, 2023, 2:00p.m.* at the *new BAC Conference Office, at the back of Agro-Sports*

Center, J. Lukban Street, Daet, Camarines Norte, which shall be open to prospective bidders.

- 7. Bids must be duly received by the BAC Secretariat through manual submission at the address below on or before *March 21, 2023 at 1:30p.m.* Late bids shall not be accepted.
- 8. All bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in **ITB** Clause 14.
- 9. Bid opening shall be on *March 21, 2023 at 2:00p.m.* at the *new BAC Conference Office*, at the back of Agro-Sports Center, J. Lukban Street, Daet, Camarines Norte. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.
- 10. The *Provincial Government of Camarines Norte* reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35 and 41 of the revised IRR of RA 9184 without thereby incurring any liability to the affected bidder or bidders.
- 11. For further information, please refer to:

MRS. MERCEDES M. ALFUERTE Provincial Budget Officer / BAC Chairperson Provincial Capitol Bldg., Daet, Camarines Norte (054) 885-1474

12. You may visit the website:

Philippine Government Electronic Procurement System (PhilGEPS)

MERCETES M. ALFUERTE |
Provincial Budget Officer / BAC Chairperson

Section II. Instructions to Bidders

1. Scope of Bid

The Procuring Entity, *Provincial Government of Camarines Norte* wishes to receive Bids for the *Supply & Delivery of Hospital Equipment (OR lights & 4 others)* with identification number [PR No. 23010110].

[Note: The Project Identification Number is assigned by the Procuring Entity based on its own coding scheme and is not the same as the PhilGEPS reference number, which is generated after the posting of the bid opportunity on the PhilGEPS website.]

The Procurement Project (referred to herein as "Project") is composed of **Five (5) items**, the details of which are described in Section VII (Technical Specifications).

2. Funding Information

- 2.1. The GOP through the source of funding as indicated below for 2023 in the amount of *NINE MILLION NINE HUNDRED FIFTY SEVEN THOUSAND SEVEN HUNDRED TWENTY PESOS (P9,957,720.00)*
- 2.2. The source of funding is the Approved Capital Outlay CY-2023

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. Foreign ownership limited to those allowed under the rules may participate in this Project.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:
 - a. For the procurement of Non-expendable Supplies and Services: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
 - b. For the procurement of Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty-five percent (25%) of the ABC.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under ITB Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that subcontracting is not allowed.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address as indicated in paragraph 6 of the **IB**.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause 5.3 should have been completed within 5 years prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in **Section VIII (Checklist of Technical and Financial Documents)**.
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, ex-warehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;

- iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
- iv. The price of other (incidental) services, if any, listed in e.

b. For Goods offered from abroad:

- i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
- ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications).**

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in Philippine Pesos.

14. Bid Security

- 14.1. The Bidder shall submit a Bid Securing Declaration¹ or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.
- 14.2. The Bid and bid security shall in no case exceed One Hundred Twenty (120) calendar days from the opening of the bid. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

¹ In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time and either at its physical address as indicated in paragraph 7 of the **IB**.

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "passed," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII (Technical Specifications)**, although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.

- 19.4. The Project shall be awarded as One Project having several items that shall be awarded as one contract.
- 19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

20.1. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**.

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

Section III. Bid Data Sheet

Bid Data Sheet

| ITB | |
|--------|--|
| Clause | |
| 5.3 | For this purpose, contracts similar to the Project shall be: |
| | a) The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty five percent (25%) of the ABC. |
| | b) completed within 5 years prior to the deadline for the submission and receipt of bids. |
| 7.1 | Subcontracting is not allowed. |
| 12 | The price of the Goods shall be quoted DDP <i>Daet, Camarines Norte</i> or the applicable International Commercial Terms (INCOTERMS) for this Project. |
| 14.1 | The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: |
| | a. The amount of not less than 2% of the ABC or <i>P 199,154.40</i> if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or |
| | b. The amount of not less than 5% of the ABC or <i>P</i> 497,886.00, if bid security is in Surety Bond. |
| 19.3 | The $lot(s)$ and $item(s)$ is/are: |
| | PR# 23010110- Supply and Delivery of Hospital Equipment (OR lights & 4 others) |
| 20.2 | The LCB shall submit the following documentary requirements within a nonextendible period of five (5) calendar days from receipt of the notification; |
| | (a) Latest Annual Income and Business Tax Return (per Revenue Regulations 3-2005); |
| | (b) License to Operate (LTO) as distributor, manufacturer, wholesaler or importer but NOT RETAILER; |
| | (e) Certificate(s) of Product Registration (CPR) issued by FDA for the brand offered for all registerable items; If the CPR is expired, the bidder must attach the expired CPR together with the receipt or proof of renewal. However, for new application of CPR, official receipt or certificate of ongoing processing will not be accepted; |
| | (f) Material Safety Data Sheets |
| 21.2 | Not Applicable. |

Section IV. General Conditions of Contract

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the SCC.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184.

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the SCC, Section IV (Technical Specifications) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

- 6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Special Conditions of Contract

| 000 | Special Conditions of Contract |
|---------------|--|
| GCC Clause | |
| 1 | Delivery and Documents – |
| | The delivery terms applicable to this Contract are delivered <i>to Daet, Camarines Norte</i> . Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination. |
| | Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements). |
| | For purposes of this Clause the Procuring Entity's Representative at the Project Site are the <i>End User</i> and the <i>Inspectorate Team</i> . |
| | Incidental Services – |
| | The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements: |
| | a. performance or supervision of on-site assembly and/or start-up of the supplied Goods; b. furnishing of tools required for assembly and/or maintenance of the supplied Goods; c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods; d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods. The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services. |
| | Packaging |
| | The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the |

remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

Name of the Procuring Entity

Name of the Supplier

Contract Description

Final Destination

Gross weight

Any special lifting instructions

Any special handling instructions

Any relevant HAZCHEM classifications

A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging

Transportation -

Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.

Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.

Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, Goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, Goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure.

| | The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination. |
|-----|---|
| | Intellectual Property Rights – |
| | The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof. |
| 2.2 | Partial Payment is not allowed. |
| 4 | The inspections and tests that will be conducted are: |
| | 1) Upon delivery, the Goods shall undergo preliminary physical inspection by the Inspection Team of the PROCURING ENTITY to ascertain the physical condition and acceptability of the Goods. |
| | 2.) The supplier shall promptly replace the equivalent quantity of Goods taken as samples without cost to the PROCURING ENTITY. |

Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

| Item Number | Description | Quantity | Total | Delivered, Weeks/Months |
|----------------|--|----------|-------|--|
| 1 lot | Supply and Delivery of Hospital Equipment (OR Lights & 4 others) | | | Items shall be delivered 60 calendar days after receipt of NTP |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Section VII. Technical Specifications

Technical Specifications

| Item | Specification | on | | Statement of Compliance |
|------|--|---|---|-------------------------|
| 1 | OR Lights | | | |
| | (efficient & economic: incredible to 60,000 hours, central illumi 130,000 lux, adjustable light fiel depth of illumination 1200mm, lo patient monitor / advanced per advanced measurements, huge battery working time, easy to us friendly interfaces, unique acc durability; high quality accessor 0.75m drop protection and 11 compatible with multiple cleaning | nation 16d diameter w power corformance: data cape; hr/bp aressory caries, drop | 0,000 lux / c, maximum onsumption, essentially acity, long halysis, user binet, high protection - | |
| | Natural "cold light" with no Combined with an Ondal sp mobility and ensures stability, perfectly integrated into lamina concentrically circular design of design minimizes the turbuler sterile conditions. (certified per Dand less costly maintenance, individual circuit can be replaced will maximize the maintenance of for easier control. Ultra thinmaneuverability Ergonomic and than 12 kg double -hollow docompact design DIN-1946 part option for HDR camera integration. | ring arm Original ar flow, the for better ace, and al OIN-1946 p ach LED acd respect cost, touch a design & compact esign ergo 4 certifie | maximizes and unique e Ultra-thin hygiene, the lows better art 4), easier bulb with every, which screen panel ex excellent desgin less onomic and d.(12-2008) | |
| | TECHNICAL SPECIFICATIONS | 1ST LIGHT | 2ND LIGHT | |
| | Central illuminance (at 1m distance) | ARM 160,000 | ARM 130,000 lux, | |
| | Light field diameter (at 1am distance) depth of illumination (L1 + L2) Correlated color temperature | lux 180~300m m 1,200mm 4,350k | 180~270mm ,1, 200mm, 4,350k, | |
| | Color rendering index (Ra) Colore rendering index (R9) Shadow dilution with tube | 96 97 100% | 96, 97, 100% | |
| | Shadow dilution with one mask Shadow dilution with tube and one mask Shadow dilution with two mask | 75 70% 55% | 70% 65% 55% | |
| | Shadow dilution with tube and two masks Ambient illumination Service life of bulb | 50% 8,000 lux >60,000h | 50% 6,500 lux, >60,000h, | |
| | Bulb power consumption | 85W, 100~240 VAC, 50/60 Hz | 65W, 100~240 VAC, 50/60 Hz | |
| | Power supply | | | |
| | | | | |
| | Number of LED bulbs Dimming range | 32 5~100% | 24, 5~100%, | |

PATIENT MONITOR SPECIFICATIONS

Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800*600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, w/o recorder), touch screen

Parameters: Support monitoring of ECG, Resp, NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg AVR 15-260mmHg, pediatric: SYS: 25-240mmHg DIA: 10-115mmHg AVR: 15-215mmHg, Neonatal: SYS: 25-140mmHg DIa: 10-115mmHg AVR: 15-125mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis.

System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports powerdown storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc.. three default configurations adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof.

| | Operation Stool 350x (500-7500) caster | |
|---|---|--|
| | Operation Stool Soux (Sou-7300) Caster | |
| 2 | (All stainless steel 304 construction, stainless steel 304 | |
| | round seat with mounted cork, height adjustable rund seat with screw, four legs with round foot rest, four legs | |
| | with round foot or 2" swivel caster) | |
| | , | |
| | Laryngoscope (Fiberoptic) | |
| | (Consist of macintosh blade #1, #2, #3, #4 soft pouch) | |
| | Solids handles made of chromium plated metal. * Fluted handle surface for hygeinic usage and a secure | |
| | grip in the hand | |
| | * Practically wear-free, standard holding fixture for the | |
| | blade *Solid metal contact for reliable activation of | |
| | illumination | |
| | *Handle diameter type C 28mm,non rechargeable,uses | |
| | type C battery *All blades are compatible with handles complying with | |
| | ISO 7376 | |
| | *With LED 3.5 V or 2.5 V xenon lamp for bright, white | |
| | light *Lamp integrated into the handle with metal contacts | |
| 3 | simplifies | |
| | autoclaving of the blades *Optimum light transmission with extra strong fiber | |
| | bundles | |
| | *Macintosh F.O blades with integrated light conductor | |
| | *Long service life with autoclaving cycles of 134 C for 5 minutes | |
| | *Stainless steel blades with refined surface finish,easy | |
| | to clean blade surface | |
| | *Special blade designs offer excellent visibility of the vocal chords and | |
| | epiglottis and simplify insertion of the endotracheal tube | |
| | *Soft cases are available for individual combinations of | |
| | up to five blades | |
| | and one handle | |
| | MAC 1 blade length 95mm MAC 1 blade length 116mm | |
| | MAC 1 blade length 133mm | |
| | MAC 1 blade length 155mm Portable Aspirator | |
| | rortable Aspirator | |
| | (Portable Battery 400, 1L collecting bottle, 0-600/650 | |
| | mmHg vacuum power (at sea level), easy monitoring vacuum meter adjusting the vacuum value, flow | |
| 4 | (airflow): 20 lt/min, dual safety that prevents liquid from | |
| | running into the pump, sterile, transparent jar with | |
| | autoclave, signal lamps showing device operation, electric network availability and battery status, silent, | |
| | dry vacuum pump maintenance and periodic oiling not | |
| | required, pump motor speed 2500 rpm/min, metal anti- | |

| | rust epoxy polyester powder formace paint for durable body, painted with silver ion technology and antimicrobial effect, mobile five-wheeled polished aluminum spider foot option, supply voltage 110/230V, 50/60 Hz, can operate with battery for 60mins without the need for connected power, dimensions, device 345 x 250 x 305mm, stand Ø620mm, height 720mm, device 7.5kg, with stand 14kg) | |
|---|--|--|
| 5 | Operation Stool 350x (500-750) not movable (All stainless steel 304 construction, stainless steel 304 round seat with mounted cork, height adjustable round seat with strong and accurate screw) | |
| | | |

[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]

Section VIII. Checklist of Technical and Financial Documents

Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE

| | | Class "A" Documents |
|-----|--------|--|
| Leg | gal Do | <u>cuments</u> |
| | (a) | Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages); and |
| | (b) | Registration certificate from Securities and Exchange Commission (SEC), Department of Trade and Industry (DTI) for sole proprietorship, or Cooperative Development Authority (CDA) for cooperatives or its equivalent document, and |
| | (c) | Mayor's or Business permit issued by the city or municipality where the principal place of business of the prospective bidder is located, or the equivalent document for Exclusive Economic Zones or Areas; and |
| | (d) | Tax clearance per E.O. No. 398, s. 2005, as finally reviewed and approved by the Bureau of Internal Revenue (BIR). |
| | | (Note: All Legal Documents must be Certified True Copy) |
| Teo | chnica | l Documents |
| | (f) | Statement of the prospective bidder of all its ongoing government and private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be bid; and |
| | (g) | Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the |
| | (h) | relevant period as provided in the Bidding Documents; <u>and</u> Original copy of Bid Security. If in the form of a Surety Bond, submit also a certification issued by the Insurance Commission; |
| | | <u>or</u> |
| | (i) | Original copy of Notarized Bid Securing Declaration; <u>and</u> Conformity with the Technical Specifications, which may include production/delivery schedule, manpower requirements, and/or aftersales/parts, if applicable; <u>and</u> |
| | (j) | Original duly signed Omnibus Sworn Statement (OSS); and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder. |
| Ti | | |

Financial Documents

The Supplier's audited financial statements, showing, among others, the Supplier's total and current assets and liabilities, stamped "received" by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission (certified true copy); and

| | | (1) | The prospective bidder's computation of Net Financial Contracting Capacity (NFCC); |
|----|-------------|-------------------|---|
| | | | or A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation. |
| | | | Class "B" Documents |
| | | (m) | If applicable, a duly signed joint venture agreement (JVA) in case the joint venture is already in existence; |
| | | | or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful. |
| | Ωdl | an da | cum entam requirements un der DA No. 0194 (ag amplicable) |
| | | (n) | cumentary requirements under RA No. 9184 (as applicable) [For foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government |
| | | (o) | office of their country stating that Filipinos are allowed to participate in government procurement activities for the same item or product. Certification from the DTI if the Bidder claims preference as a Domestic Bidder or Domestic Entity. |
| 25 | FIN | (a) (b) (c) | CIAL COMPONENT ENVELOPE Original of duly signed and accomplished Financial Bid Form Original of duly signed and accomplished Price Schedule(s); and Bid Proposals |
| | | () | 1 |

Bid Form for the Procurement of Goods

| BID FORM |
|---|
| Date: |
| Date: Project Identification No.: |
| To: [name and address of Procuring Entity] |
| Having examined the Philippine Bidding Documents (PBDs) including the Supplemental or Bid Bulletin Numbers [insert numbers], the receipt of which is hereby duly acknowledged, we, the undersigned, offer to [supply/deliver/perform] [description of the Goods] in conformity with the said PBDs for the sum of [total Bid amount in words and figures] or the total calculated bid price, as evaluated and corrected for computational errors, and other bid modifications in accordance with the Price Schedules attached herewith and made part of this Bid. The total bid price includes the cost of all taxes, such as, but not limited to: [specify the applicable taxes, e.g. (i) value added tax (VAT), (ii) income tax, (iii) local taxes, and (iv) other fiscal levies and duties], which are itemized herein or in the Price Schedules, |
| If our Bid is accepted, we undertake: |
| to deliver the goods in accordance with the delivery schedule specified in the Schedule of Requirements of the Philippine Bidding Documents (PBDs); |
| b. to provide a performance security in the form, amounts, and within the times prescribed in the PBDs; |
| c. to abide by the Bid Validity Period specified in the PBDs and it shall remain binding upon us at any time before the expiration of that period. |
| [Insert this paragraph if Foreign-Assisted Project with the Development Partner: Commissions or gratuities, if any, paid or to be paid by us to agents relating to this Bid, and to contract execution if we are awarded the contract, are listed below: |
| Name and address Amount and Purpose of of agent Currency Commission or gratuity |
| |
| (if none, state "None")] |

Until a formal Contract is prepared and executed, this Bid, together with your written acceptance thereof and your Notice of Award, shall be binding upon us.

We understand that you are not bound to accept the Lowest Calculated Bid or any Bid you may receive.

We certify/confirm that we comply with the eligibility requirements pursuant to the PBDs.

The undersigned is authorized to submit the bid on behalf of [name of the bidder] as evidenced by the attached [state the written authority].

We acknowledge that failure to sign each and every page of this Bid Form, including the attached Schedule of Prices, shall be a ground for the rejection of our bid.

| Name: | |
|--|--|
| Legal capacity: | |
| Signature: | |
| Duly authorized to sign the Bid for and behalf of: | |
| Date: | |

Bid Securing Declaration Form

[shall be submitted with the Bid if bidder opts to provide this form of bid security]

| REPUBLIC OF THE PHILIPPINES) | |
|------------------------------|--------|
| CITY OF |) S.S. |

BID SECURING DECLARATION Project Identification No.: [Insert number]

To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- 1. I/We understand that, according to your conditions, bids must be supported by a Bid Security, which may be in the form of a Bid Securing Declaration.
- 2. I/We accept that: (a) I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of two (2) years upon receipt of your Blacklisting Order; and, (b) I/we will pay the applicable fine provided under Section 6 of the Guidelines on the Use of Bid Securing Declaration, within fifteen (15) days from receipt of the written demand by the procuring entity for the commission of acts resulting to the enforcement of the bid securing declaration under Sections 23.1(b), 34.2, 40.1 and 69.1, except 69.1(f),of the IRR of RA No. 9184; without prejudice to other legal action the government may undertake.
- 3. I/We understand that this Bid Securing Declaration shall cease to be valid on the following circumstances:
 - a. Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
 - b. I am/we are declared ineligible or post-disqualified upon receipt of your notice to such effect, and (i) I/we failed to timely file a request for reconsideration or (ii) I/we filed a waiver to avail of said right; and
 - c. I am/we are declared the bidder with the Lowest Calculated Responsive Bid, and I/we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this ____ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]
[Insert signatory's legal capacity]
Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Omnibus Sworn Statement

[shall be submitted with the Bid]

| REPUBLIC OF THE PHILIPPINES |) | |
|-----------------------------|---|------|
| CITY/MUNICIPALITY OF |) | S.S. |

AFFIDAVIT

- I, [Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:
- 1. [Select one, delete the other:]

[If a sole proprietorship:] I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];

[If a partnership, corporation, cooperative, or joint venture:] I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];

2. [Select one, delete the other:]

[If a sole proprietorship:] As the owner and sole proprietor, or authorized representative of [Name of Bidder], I have full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached duly notarized Special Power of Attorney;

[If a partnership, corporation, cooperative, or joint venture:] I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the [Name of the Procuring Entity], as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];

- 3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;
- 4. Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- 5. [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;
- 6. [Select one, delete the rest:]

[If a sole proprietorship:] The owner or sole proprietor is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

[If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

- 7. [Name of Bidder] complies with existing labor laws and standards; and
- 8. [Name of Bidder] is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
 - a. Carefully examining all of the Bidding Documents;
 - b. Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract:
 - c. Making an estimate of the facilities available and needed for the contract to be bid, if any; and
 - d. Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- 9. [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

| IN | WITNESS | WHEREOF, | have | hereunto | set | my | hand | this | day | of | , | 20 | at |
|----|--|--------------|------|----------|-----|----|------|------|---------|----|---|----|----|
| | ······································ | Philippines. | | | | | | | | | | | |

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]
[Insert signatory's legal capacity]
Affiant

ruat]

[Jurat]
[Format shall be based on the latest Rules on Notarial Practice]

Performance Securing Declaration (Revised)

[if used as an alternative performance security but it is not required to be submitted with the Bid, as it shall be submitted within ten (10) days after receiving the Notice of Award]

PERFORMANCE SECURING DECLARATION

Invitation to Bid: [Insert Reference Number indicated in the Bidding Documents] To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- 1. I/We understand that, according to your conditions, to guarantee the faithful performance by the supplier/distributor/manufacturer/contractor/consultant of its obligations under the Contract, I/we shall submit a Performance Securing Declaration within a maximum period of ten (10) calendar days from the receipt of the Notice of Award prior to the signing of the Contract.
- 2. I/We accept that: I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of one (1) year for the first offense, or two (2) years for the second offense, upon receipt of your Blacklisting Order if I/We have violated my/our obligations under the Contract;
- 3. I/We understand that this Performance Securing Declaration shall cease to be valid upon:
 - a. issuance by the Procuring Entity of the Certificate of Final Acceptance, subject to the following conditions:
 - i. Procuring Entity has no claims filed against the contract awardee;
 - ii. It has no claims for labor and materials filed against the contractor; and
 - iii. Other terms of the contract; or
 - b. replacement by the winning bidder of the submitted PSD with a performance security in any of the prescribed forms under Section 39.2 of the 2016 revised IRR of RA No. 9184 as required by the end-user.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this _____ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]
[Insert signatory's legal capacity]
Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice

Standard Form Number: SF-GOODS-13a

Business Name:

LIST OF ALL ON-GOING GOVERNMENT & PRIVATE CONTRACTS

INCLUDING CONTRACTS AWARDED BUT NOT YET STARTED

| a. Date Awarded b. Date started c. Date of | % of Accomplishment | | Accomplishment | | Value of Outstanding Works/ Undelivered Portion |
|--|---------------------|------------------------|---|--|---|
| o o mpretion | . iai ii ia | 710144 | . 6.4.611 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | b. Date started | b. Date started Accomp | b. Date started Accomplishment c. Date of | | |

Note: This statement shall be supported with:

- 1. Notice of Award and/or Contract
- Notice to Proceed Issued by the owner
- 3. Certificate of Accomplishment signed by the owner or authorized representative

| Submitted by | : |
|--------------|---|
| Designation | : |
| Date | : |

STATEMENT OF SINGLE LARGEST CONTRACT COMPLETED WHICH ARE SIMILAR IN NATURE

· _____

| Business Ad | Business Address : | | | | | | | | | |
|--------------------|--------------------|-------------------|---------------|---|----------------------------|------------------------|--|--|--|--|
| | | | | | | | | | | |
| | a. Owner's Name | | Bidder's Role | 1 | a. Amount Awarded | a. Date Awarded | | | | |
| Name of Contracts/ | b. Address | Nature of Work | Description | % | b. Amount of Completion | b.Contract Effectivity | | | | |
| | c. Telephone Nos. | | | | c. Duration | c. Date Completed | | | | |
| GOVERNMENT | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| PRIVATE | | | | | | | | | | |
| PRIVAIE | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | • | | | | | | | | | |

Submitted by : _____

Note: This statement shall be supported with:

1. Contract

Certificate of Completion
 Certificate of Acceptance

Business Name

Designation : _____

Date : _____

Standard Form Number: SF-GOODS

NOTE:

FINANCIAL DOCUMENTS FOR ELIGIBILITY CHECK

A. Summary of the applicants Supplier's/Distributor's/Manufacturer's assets and liabilities on the basis of the attached income tax return and audited financial statement, stamped "RECEIVED" by the Bureau of Internal Revenue or BIR authorized collecting agent, For The immediately preceding year and A certified copy of Schedule of Fixed Assets particularly the list of construction equipment.

| | | Year 20 |
|---|---------------------------|---------|
| 1 | Total Assets | |
| 2 | Current Assets | |
| 3 | Total Liabilities | |
| 4 | Current Liabilities | |
| 5 | Net Worth (1-3) | |
| 6 | Net Working Capital (2-4) | |

| R | The Net Fir | nancial (| Contracting Capacity (NFCC) based on the above data is computed as follows: |
|-----|--------------|--------------|---|
| D. | THE NELTH | ianciai C | contracting Capacity (Ni CC) based on the above data is computed as follows. |
| | NFCC | = | [(current asset – current liabilities)(15)] minus value of all outstanding o uncompleted portions of the projects under ongoing contracts, including awarded contracts yet to be started. |
| | NFCC | = | p |
| | or | | |
| | | | licensed bank to extend to it a credit line if awarded to contract or a cash deposition of at least 10% of the proposed project to be bid. |
| | | | |
| Нег | | | |
| | | | by the BIR or BIR authorized collecting agent for the immediately preceding year |
| and | l cash depos | sit certific | cate or certificate of Commitment from a licensed bank to extend a credit line |
| Sul | omitted by: | | |
| | | | |
| Dat | e: | | |

1. If partnership of joint Venture, each Partner or Member Firm or Joint Venture shall submit the above requirement

| | vards Commi | | Norto | | | | |
|------------------------|-----------------|--------------|--|--------------------------------|--------------------------------------|------------------------|---------------|
| rovincial Ca | Capitol Buildin | g camarines | Norte | | | | |
| aet, Camar | rines Norte | | Popubli: | of the Philippines | | | |
| | | | | F CAMARINES NO | ORTE | | |
| | | | BIDS AND A | Daet WARDS COMMI | TTEE | | |
| | | | | | | PR No. 23010110 | |
| | | | | | | 1 K NO. 23010110 | |
| | | | | | | | |
| r: | | | | | | | |
| | d proposal | s plainly ma | arked "Proposals for P.R. No. | 23010110 | to the Provincial gove | rnment is subject to | the terms |
| nd condit | tions conta | ined at the | back hereof will be received at the Offic | e of the Bids and Awa | rds Committee, Daet, C | amarines | |
| orte on oi nd Award | | | 1, 2023 and will be publicly opened sence of the bidders or their authorized | | 2:00pm | by the Member | s of the Bids |
| | | | | | | | |
| | | | | | | MERCEDES M. ALF | |
| | | | | | | BAC Chairpers | on |
| | | | BID | PROPOSALS | | | |
| ltem | Quantity | Unit | AI | RTICLES | | UNIT PRICE | AMOUNT |
| | | | | | | | |
| 1 | 5 | bundle | OR Lights | | | | |
| | | | (efficient & economic: incredible le | | | | |
| | | | central illumination 160,000 lux / ′ adjustable light field diameter, ma | | | | |
| | | | 1200mm, low power consumption | • | | | |
| | | | performance: essentially advance | ed measurements, h | nuge data capacity, | | |
| | | | long battery working time, easy to | | | | |
| | | | interfaces, unique accessory cabi accessories, drop protection - 0.7 | | | | |
| | | | resistance, compatible with multip | | | | |
| | | | | | | | |
| | | | Natural "cold light" with no infrare | d components. Con | nbined with an | | |
| | | | Ondal spring arm maximizes mobi | • | | | |
| | | | unique perfectly integrated into la circular design for better hygiene | | | | |
| | | | turbulence,and allows better steri | | | | |
| | | | part 4),easier and less costly mai | | | | |
| | | | individual circuit can be replaced maintenance cost,touch screen p | | | | |
| | | | design & excellent maneuverabilit | | | | |
| | | | than 12 kg double -hollow design | | | | |
| | | | 1946 part 4 certified.(12-2008) op | otion for HDR came | ra integration | | |
| | | | upgrade. | | | | |
| | | | TECHNICAL SPECIFICATIONS | 1ST LIGHT ARM | 2ND LIGHT ARM | | |
| | | | Central illuminance (at 1m distance) Light | 160,000 lux | 130,000 lux, | | |
| | | | field diameter (at 1am distance) depth of | 180~300mm | 180~270mm,1, | | |
| | | | illumination (L1 + L2) Correlated color | 1,200mm | 200mm, | | |
| | | | temperature Color rendering index (Ra) | 4,350k 96 | 4,350k, 96, | | |
| | | | Colore rendering index (R9) | 97 | 97, | | |
| | | | Shadow dilution with tube | 100% | 100% | | |
| | | | Shadow dilution with one mask | 75 | 70% | | |
| | | | Shadow dilution with tube and one mask | 70% | 65% | | |
| | | | Shadow dilution with two mask | 55% | 55% | | |
| | | | Shadow dilution with tube and two masks | 50% | 50% | | |
| | | | Ambient illumination | 8,000 lux | 6,500 lux, | | |
| | 1 | | Service life of bulb | >60,000h | >60,000h, 65W, 100~240 VAC, 50/60 | | |
| | | | Bulb power consumption | 85VV, 100~240 VAC, 50/60 Hz | 65VV, 100~240 VAC, 50/60 Hz | | |
| | | | | | | | |
| | | | Pow er supply | | | | |
| | | | Number of LED bulbs | 32 | 24, | | |
| | | | Number of LED bulbs Dimming range | 5~100% | 5~100%, | | |
| | | | Number of LED bulbs | | | | |
| | | | Number of LED bulbs Dimming range | 5~100% | 5~100%, | | |
| otal | | | Number of LED bulbs Dimming range | 5~100% 600mm | 5~100%, | | |
| otal | | | Number of LED bulbs Dimming range Light head dimension | 5~100% 600mm | 5~100%, | | |
| | | | Number of LED bulbs Dimming range Light head dimension amount in word. | 5~100% 600mm | 5~100%, 600mm | | |
| I hereb | | | Number of LED bulbs Dimming range Light head dimension | 5~100% 600mm | 5~100%, 600mm | pined | |
| I hereb | | | Number of LED bulbs Dimming range Light head dimension amount in word. | 5~100% 600mm | 5~100%, 600mm | pined | |

| PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 1.2.1 inch high resolution LED screen, color resolution 800°600. up to 11 waveforms display, weigh less than 4kg with battyery (standard version, wo recorder), touch screen Parameters: Support monitoring of ECG, Resp,NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QTI/OE interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult. SYS 25-250mmly DN: 10-115mmly DN: 12-250mmly, Broatal: SYS: 25-250mmly DN: 10-115mmly DN: 12-251mmly, DR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible visual alarm and adjustable islam level; centralized alarm setu perintings, support bendynamics and dose centralized alarm setu perintings, support bendynamics and dose centralized alarm setu perintings, support femolynamics and dose centralized alarm setup perintings, support femolynamics and dose centralized alarm setup perintings. Support femolynamics and dose centralized alarm setup perintings support femolynamics and dose centralized alarm setup perintings. Support femolynamics and dose centralized alarm setup setups. Support femolynamics and dose centralized alarm setup setups. Support femolynamics and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including | | wards Committ | | | | | |
|--|------------|--|--------------|---|------------|----------------------|------------------|
| Republic of the Philippines PROVINCE OF CAMARINES NORTE Data BIDS AND AWARDS COMMITTEE PR No. 23010110 PR | ovincial (| Capitol Building | | Norte | | | |
| BIDS AND AWARDS COMMITTEE PR No. 23010110 Description of the provincial government is subject to the terms on discoss contained at the back hereof will be received at the Office of the sides and Awards Committee, Dark Comerines and one forter a Manch 1, 2023 and will be publicly opened at 200pm. by the Members of the side of Committee in the preceived the sidede or their authorited representatives. BID PROPOSALS BID PROPOSALS PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and encontal patients, 12: 11 inch high resolution LED screen, color resolution 800'800, up to 11 waveforms display, weight less than 4kg with battleyry (slandard version, wo recorder), louch screen Parameters: Support monitoring of ECG, Resp. NIBP, SpO2, PR and Temp as standard, and IBP, CO., CO2 as optional, multi-lead ECG algorithms in implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and slarmed, support ST and OT/OT is interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is commercial, wider range for NIBP and PR measurement greatly improves the accuracy of corder values monitoring if the electrode is commercial, wider range for NIBP and PR measurement greatly improves the accuracy of corder values monitoring, support ARR analysis and 24 arrhythmia events could be detected and slarmed, support ST and OT/OT is interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is commercial, wider range for NIBP and PR measurement greatly improves the accuracy of corder values monitoring if the electrode is commercial, wider range for NIBP and PR measurement greatly improves the accuracy of corder values, adult: N°S 25-25-240mmlg Dis 1-0115mmlg AVR: 15-25mmlg, Rev. 2 | iei, cam | arries Norte | | | | | |
| BIDS AND AWARDS COMMITTEE PR No. 23010110 PR MRCDES M. AFFUETE BAC Chairpers on BAC Chairpers on BAC Chairpers on Prysical Structure: Compact patient monitor, used or adult, pediatric and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800*600. up to 11 wwwforms display, weigh less than 4kg with battyery (standard version, wo recorder), touch screen Parameters: Support monitoring of ECG, Resp. NBP, SpQ2, PR and Temp as standard, and BP, C. O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and slarmed, support ST and GT/GT, in iteravial monitoring, electrode is commercial, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-200mmlg DN 10-15mmlg AVR: 15-15mmlg, Neonatais: SYS: 25-240mmlg DN: 10-115mmlg AVR: 15-125mmlg, Neonatais: SYS: 25-140mmlg Dis: 10-15mmlg AVR: 15-125mmlg, Neonatais: | | | | | | | |
| size and proposals plainty marked "Proposals for P.R. No. Descriptions contained at the back hereof will be received at the Office of the Bids and Awards Committee, Daet, Camarines and or before March 22, 2023 And will be publicly opened at BD PROPOSALS MERCEDES M. ALFUERTE BAC Chairpers on BID PROPOSALS BID PROPOSALS PATIENT MONITOR SPECIFICATIONS Physical Structure: Company patient monitor, used for adult, pediatric and neonatal patients, 12.1 Inch high resolution, LED screen, color resolution 800°600, up to 11 wewforms display, weigh less than 4kg with battyery (standard version, w/o recorder), touch screen Parameters: Support monitoring of ECG, Resp. NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and OTTOG interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult; SYS 25-200mmitg DIA 10-250mmitg AVR 15-250mmitg, Neonatal SYS: 25-140mmitg DIA 10-150mmitg AVR 15-250mmitg, Neonatal SYS: 25-140mmitg DIA 10-151mmitg AVR 15-250mmitg, Neonatal SYS: 25-140mmitg DIA 10-1151mmitg AVR 15-250mmitg, Neonatal SYS: 25-140mmitg DIA 10-151mmitg AVR 15-250mmitg, Neonatal SYS: 25-140mmitg DIA 1 | | | | | | | |
| martines contained at the back hereof will be received at the Office of the Bids and Awards Committee, Daet, Camarines of the Bid March 22, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and 1, 2023 a | | | | | F | PR No. 230101 | 10 |
| martines contained at the back hereof will be received at the Office of the Bids and Awards Committee, Daet, Camarines of the Bid March 22, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and 1, 2023 a | | | | | | | |
| martines contained at the back hereof will be received at the Office of the Bids and Awards Committee, Daet, Camarines of the Bid March 22, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and 1, 2023 a | | | | | | | |
| martines contained at the back hereof will be received at the Office of the Bids and Awards Committee, Daet, Camarines of the Bid March 22, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and will be publicly opened at 2009 by the Members of the Bid March 2, 2023 and 1, 2023 a | r: | | | | | | |
| BID PROPOSALS ARTICLES BID PROPOSALS ARTICLES ARTICLES PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatial patients, and the property of the property of the patients of the property of the patients of | | | | | | | t to the terms |
| BID PROPOSALS MINOS CONTROL OF THE | | | | | 2:00pm | by the Mem | bers of the Bids |
| BID PROPOSALS M Countity Unk ARTCLES UNIT PRICE AMOU PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800°600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, wo recorder), touch screen Parameters: Support monitoring of ECG, Resp.NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and OT/QT interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-2200mmitg DIA 10-115mmitg AVR 15-25fmmitg, Neonatal: SYS: 25-240mmitg DIA 10-115mmitg AVR 15-25fmmitg, Neonatal: SYS: 25-240mmitg DIA 10-115mmitg AVR 15-125mmitg, PR: 20-300pm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input. 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external LISB storage, supports power-down storage and data transferring is LISB drive, nurse call alarm, external display screen through VGA, support eview and storage of 1200 hours level 1300 alarms events. 1600 agricus of working time station, various monitoring interfaces including Militends, OxyCRG, large font, and standard screen acc, three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, a hours of working time standard Li-on battery, up to 8 hours of working time estandard Li-on battery, up to 8 hours of working time management effective, uni | Awar | us committee | e iii die pi | escrice of the braders of their authorized representatives. | | | |
| PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 1.2.1 inch high resolution. LED soreen, color resolution 800°600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, who recorder), touch screen Parameters: Support monitoring of ECG, Resp.NISP, SpO2, PR and Temp as standard, and ISP, C.O., CO2 as optional, multi-lead ECG algorithms and the standard of the second of the | - | | | | | | |
| PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 1.2.1 inch high resolution LED screen, color resolution 800°600, up to 11 wewforms display, weigh less than 4kg with battyery (standard version, wo recorder), touch screen with the structure of the struc | | | | | | BAC Chairp | erson |
| PATIENT MONITOR SPECIFICATIONS Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 1.2.1 inch high resolution LED screen, color resolution 800°600. up to 11 waveforms display, weigh less than 4kg with battyery (standard version, wo recorder), touch screen Parameters: Support monitoring of ECG, Resp,NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QTI/OE interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult. SYS 25-250mmly DN: 10-115mmly DN: 12-250mmly, Broatal: SYS: 25-250mmly DN: 10-115mmly DN: 12-251mmly, DR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible visual alarm and adjustable islam level; centralized alarm setu perintings, support bendynamics and dose centralized alarm setu perintings, support bendynamics and dose centralized alarm setu perintings, support femolynamics and dose centralized alarm setup perintings, support femolynamics and dose centralized alarm setup perintings. Support femolynamics and dose centralized alarm setup perintings support femolynamics and dose centralized alarm setup perintings. Support femolynamics and dose centralized alarm setup setups. Support femolynamics and dose centralized alarm setup setups. Support femolynamics and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including | | 1 | | | - | | |
| Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800r600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, w/o recorder), touch screen Parameters: Support monitoring of ECG, Resp NIBP, SpO2, PR and Temp as standard, and IBP, C. O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-2200mmitg DA 10-250mmitg AVR 15-250mmitg, pediatric SYS 25-240mmitg DA: 10-115mmitg AVR: 15-215mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-215mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-125mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-125mmitg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, entralized alarm setup settings, support therodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 44b-nour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minterneds, oxyCRG, large fort, and standard screen etc., three default configurations for adulty/pediatric/neonatal palents, support a-channel recorder, | ltem | Quantity | Unit | ARTICLES | | UNIT PRICE | AMOUN |
| Physical Structure: Compact patient monitor, used for adult, pediatric and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800r600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, w/o recorder), touch screen Parameters: Support monitoring of ECG, Resp NIBP, SpO2, PR and Temp as standard, and IBP, C. O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-2200mmitg DA 10-250mmitg AVR 15-250mmitg, pediatric SYS 25-240mmitg DA: 10-115mmitg AVR: 15-215mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-215mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-125mmitg, Neonata: SYS 25-140mmitg DIa: 10-115mmitg AVR: 15-125mmitg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, entralized alarm setup settings, support therodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 44b-nour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minterneds, oxyCRG, large fort, and standard screen etc., three default configurations for adulty/pediatric/neonatal palents, support a-channel recorder, | | | | DATIENT MONITOR OREGINATIONS | | | |
| and neonatal patients, 12.1 inch high resolution LED screen, color resolution 800°600, up to 11 waveforms display, weigh less than 4kg with battyery (standard version, w/o recorder), touch screen Parameters: Support monitoring of ECG, Resp.NIBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and GT/GT interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg DIA 15-250mmHg, Neonatal: SYS: 25-240mmHg DIA 10-250mmHg DIA 17-520mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg DIA: 15-155mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg DIA: 15-155mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner injout, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hermodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VOA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms. Wew other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minterneds, OxyCRG, large forih, and standard screen etc., three default configurations for adulty/pediatric/heannal apatient, support a-channel recorder, support external network printer, up to 8 hours of working time with optional large capacity Li-o hattery, up to 8 hours of working time wi | | | | | atric | | |
| with battyery (standard version, w/o recorder), touch screen Parameters: Support monitoring of ECG, Resp.NiBP, SpO2, PR and Temp as standard, and IBP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/GTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NiBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25- 290mmHg DIA 10-115mmHg AVR. 15-250mmHg, pediatric: SYS: 25- 240mmHg DIA: 10-115mmHg AVR. 15-125mmHg, Pediatric: SYS: 25- 140mmHg DIA: 10-115mmHg AVR. 15-125mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NiBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audibe/visual alarm and adjustable alarm level, centralized alarm setup settings, support bemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support treview and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NiBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRQ, large font, and standard screen etc., three default configurations or and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, | | | | | | | |
| Parameters: Support monitoring of ECG, Resp, NIBP, SpO2, PR and Temp as standard, and ISP, C.O., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and OT/OTC interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatty improves the accuracy of border values, adult: SYS 25- 290mmHg Dix 10-250mmHg AVR 15-250mmHg, pediatric: SYS: 25- 290mmHg Dix 10-115mmHg AVR: 15-215mmHg, Neonatai: SYS: 25- 140mmHg Dix: 10-115mmHg AVR: 15-125mmHg, Neonatai: SYS: 25- 140mmHg Dix: 10-115mmHg AVR: 15-125mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level; centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three defanition for adultylypediatric/neonatal patient, support customized configurations and transferring configuration via USB drive. A hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large becapacity5G/2.4G dual band WiFi card, support wied/wireless accessories management effective, injuse integrated storage cabinet makes accessori | | | | , , | 4kg | | |
| Temp as standard, and IBP, C.Ö., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmlkg DIA: 10-250mmlkg AVR: 15-265mmlkg, Reonatal: SYS: 25-240mmlkg DIA: 10-115mmlkg AVR: 15-215mmlkg, Reonatal: SYS: 25-140mmlkg DIA: 10-115mmlkg AVR: 15-215mmlkg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring ut USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Miniternels, OxyCRG, large font, and standard screen etc., three default configurations for adultylypediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large beapacity5G/2.45 dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVison central station, support acherance makes accessories management effective, I | | | | with battyery (standard version, wo recorder), touch screen | ļ | | |
| Temp as standard, and IBP, C.Ö., CO2 as optional, multi-lead ECG algorithm is implemented to analyze the ECG signals from multiple leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmlkg DIA: 10-250mmlkg AVR: 15-265mmlkg, Reonatal: SYS: 25-240mmlkg DIA: 10-115mmlkg AVR: 15-215mmlkg, Reonatal: SYS: 25-140mmlkg DIA: 10-115mmlkg AVR: 15-215mmlkg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring ut USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Miniternels, OxyCRG, large font, and standard screen etc., three default configurations for adultylypediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large beapacity5G/2.45 dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVison central station, support acherance makes accessories management effective, I | | | | Parameters: Support monitoring of ECG, Deep NIRD, ShO2, DD o | nd | | |
| leads to ensure the measurement accuracy when one lead is interfered, support ARR analysis and 24 arrivhytmia events could be detected and alarmed, support ST and QT/QTc interval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NiBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg AVR 15-265mmHg, pecialistic SYS: 25-240mmHg DIA: 10-115mmHg AVR: 15-215mmHg, Reconatal: SYS: 25-140mmHg DIA: 10-115mmHg AVR: 15-215mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NiBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring us USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time standard Li-on battery, up to 8 hours of working time measurement effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, in the prices quoted are hereby offered. | | | | | | | |
| interfered, support ARR analysis and 24 arrhythmia events could be detected and alarmed, support ST and OT/OT cinterval monitoring, smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg AVR 15-260mmHg, pediatric: SYS: 25-240mmHg DIA: 10-115mmHg AVR: 15-215mmHg, pediatric: SYS: 25-140mmHg DIa: 10-115mmHg AVR: 15-215mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adultylypediatric-meonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working ime with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional management effective, IPX1 water-proof. | | | | | е | | |
| smart lead-off detection enables the continues monitoring if the electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg AVR 15-260mmHg, pediatric: SYS: 25-240mmHg DIA: 10-115mmHg AVR: 15-215mmHg, pediatric: SYS: 25-140mmHg DIa: 10-115mmHg AVR: 15-215mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large becapacity SG2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no find design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, inpXI water-proof. | | | | • | be | | |
| electrode is connected, wider range for NIBP and PR measurement greatly improves the accuracy of border values, adult: SYS 25-290mmHg DIA 10-250mmHg AVR 15-260mmHg, pediatric: SYS: 25-240mmHg DIA: 10-115mmHg AVR: 15-260mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg AVR: 15-215mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg AVR: 15-215mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg AVR: 15-125mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-115mmHg AVR: 15-125mmHg, Neonatal: SYS: 25-140mmHg DIA: 10-15mmHg AVR: 15-125mmHg, Neonatal: SYS: 25-140mmHg AVR: 15-125mmHg, Neonatal: SYS: 25-14 | | | | | ıg, | | |
| greatly improves the accuracy of border values, adult: SYS 25- 290mmHg DIA 10-250mmHg AVR 15-260mmHg, pediatric: SYS: 25- 240mmHg DIA: 10-115mmHg AVR: 15-215mmHg, Neonatal: SYS: 25- 140mmHig DIA: 10-115mmHg AVR: 15-125mmHg, Neonatal: SYS: 25- 140mmHig DIA: 10-115mmHg AVR: 15-125mmHg, Neonatal: SYS: 25- 140mmHig DIA: 10-115mmHg AVR: 15-125mmHg, Neonatal: SYS: 25- 140mmHig DIA: 10-115mmHig AVR: 15-125mmHig, Neonatal: Sys: 25- 140mmHig DIA: 10-115mmHig AVR: 10-1 | | | | _ | nt | | |
| 240mmHg Dla: 10-115mmHg AVR: 15-215mmHg, Neonatal: SYS: 25- 140mmHg Dla: 10-115mmHg AVR: 15-125mmHg, PR: 20-300bpm, support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1800 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Miniternads, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large becapacity SG/2 dd dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, inquie integrated storage cabinet makes accessories management effective, inquie integrated storage cabinet makes accessories management effective, inquie integrated storage cabinet makes accessories management effective and unique integrated storage cabinet makes accessories management effective and the prices quoted are hereby offered. | | | | greatly improves the accuracy of border values, adult: SYS 25- | | | |
| support heart rate analysis and dynamic NIBP analysis. System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adultylypediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time standard Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| System functions: English/Chinese display, support bar code scanner input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time between the standard Li-on battery, up to 8 hours of working time distandard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time between the standard Li-on battery, up to 8 hours of working time distandard benevity of the standard Li-on battery and the secess of the support of the standard Li-on battery and Benevision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, iPX1 water-proof. | | | | 140mmHg Dla: 10-115mmHg AVR: 15-125mmHg, PR: 20-300bpm | | | |
| input, 3-level audible/visual alarm and adjustable alarm level, centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5C/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, iPX1 water-proof. | | | | support heart rate analysis and dynamic NIBP analysis. | | | |
| centralized alarm setup settings, support Hemodynamics and dose calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, iPX1 water-proof. | | | | System functions: English/Chinese display, support bar code scar | nner | | |
| calculations, optional internal/storage external USB storage, supports power-down storage and data transferring via USB drive, nurse call alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| alarm, external display screen through VGA, support review and storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| storage of 1200 hours trend, 1800 alarm events, 1600 groups of NIBP measurements, 128 ARR alarms and 48-hour full disclosure waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | all | | |
| waveforms, View other bed function enables user to check data of any patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, liPX1 water-proof. | | | | , | NIBP | | |
| patient in the samenetwork without the help of central station, various monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| monitoring interfaces including Minitrends, OxyCRG, large font, and standard screen etc., three default configurations for adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| adulty/pediatric/neonatal patient, support customized configurations and transferring configuration via USB drive, 4 hours of working time standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiiFi card, support wied/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | nd | | |
| standard Li-on battery, up to 8 hours of working time with optional large capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | ns | | |
| capacity Li-on battery, optional intenal large bcapacity5G/2.4G dual band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| band WiFi card, support wried/wireless access to Hypervisor VI and BeneVision central station, support 3-channel recorder, support external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | | | | |
| external network printer, no fan design, remarkably reduces noise, unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. | | | | band WiFi card, support wried/wireless access to Hypervisor VI ar | | | |
| unique integrated storage cabinet makes accessories management effective, unique integrated storage cabinet makes accessories management effective, IPX1 water-proof. amount in words I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | | _ [| | |
| management effective, IPX1 water-proof. amount in words I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | unique integrated storage cabinet makes accessories manageme | | | |
| amount in words I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | | | | |
| I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | Inanagement enective, if AT water-proof. | ŀ | | |
| I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | | | | |
| I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | | | | | | | |
| I hereby certify that the above mentioned articles are actually available on my stock. The terms and conditions contained back hereof are hereby accepted and the prices quoted are hereby offered. | otal | | | amount in words | | | |
| eback hereof are hereby accepted and the prices quoted are hereby offered. | | | | uniount ii words | | | |
| eback hereof are hereby accepted and the prices quoted are hereby offered. | Iher | phy certify the | at the above | we mentioned articles are actually available on my stock. The terms and condition | ns conto | ined | |
| | | | | | , is conta | cu | |
| | | | | | | | |
| Firm/Supplier/Dealer/Contractor page 2 | - | | | Firm/Supplier/Dealer/Contractor | | | page 2 of |

| | wards Commi | | | | |
|--------------|--------------|-------------|---|------------------------|-----------------|
| Provincial (| Government o | | s Norte | | |
| ⊔aet, Cam | arines Norte | | Republic of the Philippines | | |
| | | | PROVINCE OF CAMARINES NORTE Daet | | |
| | | | BIDS AND AWARDS COMMITTEE | | |
| | | | | PR No. 23010110 | |
| | | | | | |
| | | | | | |
| Sir: | nd proposal | s plainly p | narked "Proposals for P.R. No. 23010110 to the Provincial gove | ornment is subject t | o the terms |
| and cond | tions conta | ined at the | back hereof will be received at the Office of the Bids and Awards Committee, Daet, C | Camarines | |
| Norte on o | | | 21, 2023 and will be publicly opened at 2:00pm resence of the bidders or their authorized representatives. | by the Membe | ers of the Bids |
| | | | | MERCEDES M. A | ELIERTE |
| | | | | BAC Chairper | |
| | | | BID PROPOSALS | | |
| ltem | Quantity | Unit | ARTICLES | UNIT PRICE | AMOUNT |
| | | | | | |
| 2 | 10 | unit | Operation Stool 350x (500-750)mm caster | | |
| | | | (All stainless steel 304 construction, stainless steel 304 round seat with mounted cork, height adjustable rund seat with screw, four legs with | | |
| | | | round foot rest, four legs with round foot or 2" swivel caster) | | |
| | | | | | |
| 3 | 5 | set | Laryngoscope (Fiberoptic) (Consist of macintosh blade #1, #2, #3, #4 soft pouch) | | |
| | | | Solids handles made of chromium plated metal. | | |
| | | | * Fluted handle surface for hygeinic usage and a secure grip in the hand | | |
| | | | * Practically wear-free, standard holding fixture for the blade *Solid metal contact for reliable activation of illumination | | |
| | | | *Handle diameter type C 28mm,non rechargeable,uses type C battery | | |
| | | | *All blades are compatible with handles complying with ISO 7376 | | |
| | | | *With LED 3.5 V or 2.5 V xenon lamp for bright, white light *Lamp integrated into the handle with metal contacts simplifies | | |
| | | | autoclaving of the blades | | |
| | | | *Optimum light transmission with extra strong fiber bundles | | |
| | | | *Macintosh F.O blades with integrated light conductor *Long service life with autoclaving cycles of 134 C for 5 minutes | | |
| | | | *Stainless steel blades with refined surface finish,easy to clean blade sur | r | |
| | | | *Special blade designs offer excellent visibility of the vocal chords and | | |
| | | | epiglottis and simplify insertion of the endotracheal tube *Soft cases are available for individual combinations of up to five blades | | |
| | | | and one handle | | |
| | | | MAC 1 blade length 95mm | | |
| | | | MAC 1 blade length 116mm MAC 1 blade length 133mm | | |
| | | | MAC 1 blade length 155mm | | |
| 4 | 5 | unit | Portable Aspirator 1L with Stand | | |
| | | | (Portable Battery 400, 1L collecting bottle, 0-600/650 mmHg vacuum power (at sea level), easy monitoring vacuum meter adjusting the | | |
| | | | vacuum value, flow (airflow): 20 lt/min, dual safety that prevents liquid | | |
| | | | from running into the pump, sterile, transparent jar with autoclave, signal lamps showing device operation, electric network availability and | | |
| | | | battery status, silent, dry vacuum pump maintenance and periodic oiling | | |
| | | | not required, pump motor speed 2500 rpm/min, metal anti-rust epoxy | | |
| | | | polyester powder formace paint for durable body, painted with silver ion technology and antimicrobial effect, mobile five-wheeled polished | | |
| | | | aluminum spider foot option, supply voltage 110/230V, 50/60 Hz, can | | |
| | | | operate with battery for 60mins without the need for connected power, dimensions, device 345 x 250 x 305mm, stand Ø620mm, height 720mm, | | |
| | | | device 7.5kg, with stand 14kg) | | |
| 5 | 4 | unit | Operating stool 350x (500-750)mm not movable | | |
| | | | (All stainless steel 304 construction, stainless steel 304 round seat with | | |
| | | | mounted cork, height adjustable round seat with strong and accurate | | |
| | | | screw) | | |
| | | | | | |
| Total | | | amount in words | | 1 |
| ., | h | -446. 1 | | | |
| | | | ve mentioned articles are actually available on my stock. The terms and conditions cont epted and the prices quoted are hereby offered. | uinea | |
| | | | | | |
| | | | Firm/Supplier/Dealer/Contractor | | page 3 of 3 |

TERMS AND CONDITIONS

- 1. The invitation to bid is open to all bidders which are duly licensed suppliers, manufacturers and/or distributors.
- 1. The bidders shall submit simultaneously three (3) separated sealed envelopes, the first envelope contains the "eligibility and technical requirements", the second envelope contains the "financial documents", on or before the specified date and time of bidding.
- 2. Proposals submitted after the date and time stipulated of the bids will not be entertained.
- 3. In case of discrepancies between: a) Bid prices in figures and in words, the latter shall prevail; b) total prices and unit prices, the latter shall prevail; c) Unit cost in the detailed estimates and unit cost in the bill of quantities, the latter shall prevail.
- 4. Failure to include the required bid securities as to form and amount prescribed shall automatically disqualify. The required bid securities in the form of Bid Securing Declaration, cash or cashier's/ manager's check, bank draft/guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank shall not be less than 2% of the ABC, surety bond callable upon demand shall not be less than 5% of the ABC to be bid. (Section 27 of IRR-A of RA 9184).
- 5. Prices once quoted shall be respected. Error or mistakes in quoting is bidder's responsibility.
- 6. The successful bidder is required to post a performance security bond upon signing the contract. It should be in accordance with Section 39.2 of IRR of RA 9184.
- 7. The supplier shall be liable to pay a liquidated damage to an amount of one tenth of one percent of the remaining amount for every day of delay until such goods are finally delivered. This is in case the suppliers failed to deliver goods under the contract time within the specified delivery schedule.
- 8. Claims, protests or complaints shall be filed in the Office of the Head of the Procuring Entity accompanied by the payment of a non-refundable fee stated in Section 55.3 of the IRR of RA 9184, within seven (7) calendar days from the receipt of the party concerned of the resolution of the BAC denying its motion for reconsideration, otherwise, failure to submit within time limit shall not be considered.
- 9. The Bids and Awards Committee reserves the right to accept or reject any bid, to annul the bidding process and to reject any or all bids at any time prior to contract award, without thereby incurring any liability to the affected bidders.

(signed)

MERCEDES M. ALFUERTE

BAC Chairperson

Price Schedule for Goods Offered from Abroad

[shall be submitted with the Bid if bidder is offering goods from Abroad]

| For Goods Offered from Abroad | | | | | | | | | | | | |
|-------------------------------|--------------------------|--|---|--|--|---|---|--|--|--|--|--|
| | | | | Project II | Page of | | | | | | | |
| 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | | | | | |
| Description | Country of origin | Quantity | Unit price CIF port of entry (specify port) or CIP named place (specify border point or place of destination) | Total CIF or CIP price per item (col. 4 x 5) | Unit Price Delivered Duty Unpaid (DDU) | Unit price Delivered Duty Paid (DDP) | Total Price delivered DDP (col 4 x 8) | | | | | |
| | | | | | | | | | | | | |
| Capacity: _ are: | | | | | | | | | | | | |
| | Description Capacity: _ | Description Country of origin Capacity: | Description Country of origin Quantity Capacity: | Description Country of origin Quantity Unit price CIF port of entry (specify port) or CIP named place (specify border point or place of destination) Capacity: | Description Country of origin Quantity Unit price CIF port of entry (specify port) or CIP named place (specify border point or place of destination) (col. 4 x 5) Capacity: C | Description Country of origin Quantity Unit price CIF port of entry (specify port) or CIP named place (specify border point or place of destination) (col. 4 x 5) | Description Country of origin Quantity of origin Cip named place (specify border point or place of destination) Ciol. 4 x | | | | | |

Price Schedule for Goods Offered from Within the Philippines

[shall be submitted with the Bid if bidder is offering goods from within the Philippines]

For Goods Offered from Within the Philippines

| Name of Bidder Project ID No | | | | | | | | Page | _of | | |
|----------------------------------|-------------|----------------------|----------|-------------------------------------|---|---|--|---------------------------------------|--|--|--|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | | |
| Item | Description | Country of origin | Quantity | Unit price EXW per item | Transportation and all other costs incidental to delivery, per item | Sales and other taxes payable if Contract is awarded, per item | Cost of Incidental Services, if applicable, per item | Total Price, per unit (col 5+6+7+8) | Total Price delivered Final Destination (col 9) x (col 4) | | |
| | | | | | | | | | | | |
| Name: Legal Capacity: Signature: | | | | | | | | | | | |

Duly authorized to sign the Bid for and behalf of:

